

Single Distribution Pump Assembly

High quality pump designed specifically for the high purity water industry

The Highest Quality Pump in the Industry

- Equipped with Grundfos ML motors that have the highest energy efficiency rating world-wide

Robust Heavy Duty Design

- Constructed of stainless steel for longevity

Designed Specifically for High Purity Water

- Horizontal, multi-stage distribution
- Compact with a wide range of performance
- High reliability and service friendly
- Totally enclosed fan cooled with low noise rating
- O-ring type shaft seals
- Canada and US UL Listed



| | CM5-3 Model 850202 | CM5-3 Model 850200 | CM5-6 Model 850201 | CM10-2 Model 850300 | CM10-3 Model 850301 |
|--------------------------------|--------------------------|--------------------------|--------------------------|---------------------------|---------------------------|
| Performance GPM @ PSI | 20 GPM/ 52 PSI | 20 GPM/52 PSI | 24 GPM/95 PSI | 50 GPM/51 PSI | 70 GPM/65 PSI |
| Horse Power | 1.48 | 1.48 | 3.4 | 3.4 | 5.4 |
| Phase | 1 | 3 | 3 | 3 | 3 |
| Voltage | 115 / 230 | 208/240/480 | 208/240/480 | 208/240/480 | 208/240/480 |
| Amps | 14.6 / 7.3 | 5.2 / 5.1 / 2.7 | 9.7 / 9.4 / 4.7 | 9.7 / 9.4 / 4.7 | 14.8 / 14.2 / 7.0 |
| # of Impellers | 3 | 3 | 6 | 2 | 3 |
| Housing & Impeller Material | 304 SS | 304 SS | 304 SS | 304 SS | 304 SS |
| Inlet Size, NPT | 1.25" | 1.25" | 1.25" | 1.5" | 1.5" |
| Outlet Size, NPT | 1" | 1" | 1" | 1.5" | 1.5" |
| Maximum Internal PSI | 232 | 232 | 232 | 232 | 232 |
| Country of Origin | USA | USA | USA | USA | USA |

Base Options

| | |
|--------|---|
| 890000 | Fiberglass Unistrut / Vibration Isolator Base |
| 101000 | Stainless Steel Base |